

What are the hazards and how might they harm?



Impact injuries from being hit by moving vehicles



Trip injuries from obstructions, falls on uneven ground and slopes



Impact injuries from flying objects



Back or muscle strain from manual handling

What PPE should the individual wear?





What other precautions should be taken?



Use barriers to restrict access to work areas

Working on roadsides and adjacent to highways

Safety Task Card STCBG 40

Safe System of Work

- 1. Operations within 1.5m of a live carriageway are not permitted without traffic management appropriate to type of operation and vehicle speed on carriageway.
- 2. High visibility jackets or vests must be worn at all times.
- 3. All works vehicles must be parked at least 1.5 m off the carriageway or safely within lane closures
- 4. All works vehicles must be fitted with amber flashing light which must be operated while accessing and leaving the site.
- 5. Operations must be reviewed if there are any changes in traffic patterns or weather conditions.
- 6. Ensure all equipment is secured so as not to encroach onto the public highway.
- 7. Consider prevailing wind conditions and lightweight equipment.
- 8. Ensure any site debris or operational arisings are secured so as not to encroach onto the public highway.
- 9. Plan for the safe removal of waste material.

If you have any concerns, stop and speak with your line manager before proceeding



Working on roadsides and adjacent to highways continued

Safety Task Card
STCBG 40

List any additional hazards or risks you have identified, and control measures required to manage these.